

What is claimed is:

1. A table comprising:

a support leg having an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end communicating with a top of said support leg;

a catch member extending across at least a portion of said channel; and

a worksurface supported by said top of said support leg.

2. The table of claim 1 wherein said worksurface further

comprises a cutout, wherein said top of said support leg is connected to said worksurface at said cutout.

3. The table of claim 1 wherein said top of said support leg further

comprises a socket, wherein a portion of said worksurface is received in said socket.

4. The table of claim 1 wherein said top of said support leg further

comprises a support platform, wherein a bottom of said worksurface is supported on said support platform.

5. The table of claim 1 wherein said worksurface comprises a

inwardly extending groove formed around at least a portion of the periphery thereof, and further comprising a bumper having an insert inserted into said groove.

6. The table of claim 1 wherein said channel has a first depth at a

first location proximate said top of said support leg and wherein said channel has a second depth at a second location distal to said top of said support leg, wherein said first depth is greater than said second depth.

7. The table of claim 1 wherein said channel is defined by a depth, and wherein said depth of said channel is tapered along the length thereof.

8. The table of claim 1 wherein said support leg has an opening formed along one side of said channel, and wherein said catch member  
5 comprises an insert portion inserted in said opening and a cross member extending from said insert portion across at least a portion of said channel.

9. The table of claim 8 wherein said opening in said support leg is a first opening, and wherein said support leg has a second opening formed along an opposite side of said channel opposite said first opening, and further  
10 comprising a second catch member having an insert portion inserted in said second opening and a cross member extending from said insert portion across at least a portion of said channel, wherein said cross members of said first and second catch members extend across the entirety of the channel.

10. The table of claim 1 wherein said worksurface comprises a rear  
15 edge, wherein at least a portion of said rear edge has a concave contour.

11. The table of claim 1 wherein said support leg is made of glass filled polypropylene.

12. The table of claim 1 wherein said support leg further comprises a plurality of ribs formed in said channel.

13. A table comprising:  
20 a support leg having an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end at a top of said support leg; and  
25 a worksurface supported by said top of said support leg, wherein said worksurface has a cutout shaped to receive at least a portion of said top of said support leg with at least a portion of said channel nested in said cutout.

14. The table of claim 13 wherein cutout is located at a corner of said worksurface.

5 15. The table of claim 13 wherein said top of said support leg further comprises a socket, wherein a portion of said worksurface is received in said socket.

16. The table of claim 13 wherein said top of said support leg further comprises a support platform, wherein a bottom of said worksurface is supported on said support platform.

10 17. The table of claim 13 wherein said worksurface comprises a inwardly extending groove formed around at least a portion of the periphery thereof, and further comprising a bumper having an insert inserted into said groove.

15 18. The table of claim 13 wherein said channel is defined by a depth, and wherein said depth of said channel is tapered along the length thereof.

19. The table of claim 13 further comprising a catch member extending across at least a portion of said channel.

20 20. The table of claim 19 wherein said support leg has an opening formed along one side of said channel, and wherein said catch member comprises an insert portion inserted in said opening and a cross member extending from said insert portion across at least a portion of said channel.

21. The table of claim 13 wherein said worksurface comprises a rear edge, wherein at least a portion of said rear edge has a concave contour.

25 22. The table of claim 13 wherein said support leg comprises a plurality of ribs formed in said channel.

23. The table of claim 14 wherein said channel opens diagonally outwardly from said corner of said worksurface.

24. A table comprising:  
 at least four support legs, wherein at least two of said support  
 5 legs terminate in casters and wherein at least two of said support legs  
 terminate in glides;  
 a worksurface supported by said at least four support legs.

25. The table of claim 24 wherein said at least four support legs are made of glass filled polypropylene.

10 26. The table of claim 24 wherein each of said support legs has an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end communicating with a top of said support leg.

15 27. A method for routing a utility line on a table comprising:  
 providing said table comprising a support leg having an elongated channel extending longitudinally along at least a portion of said support leg and opening laterally outwardly from said support leg, said channel having an open end at a top of said support leg, and a worksurface supported by said top of said support leg, wherein said worksurface has a  
 20 cutout shaped to receive at least a portion of said top of said support leg with at least a portion of said channel nested in said cutout;

providing a utility line having at least a portion disposed on a top of said worksurface; and  
 running said utility line from said top of said worksurface into  
 25 said channel through said open end thereof.

28. The method of claim 27 wherein said support leg comprises a catch member extending across at least a portion of said channel, and wherein said running said utility line further comprises running said utility line in said

channel behind said catch member and thereby capturing said utility line in said channel.

5           29.    The method of claim 27 wherein said worksurface comprises a rear edge at least a portion of which has a concave contour and wherein said utility line comprises a plurality of utility lines, and further comprising passing one of said plurality of utility lines from said top of said worksurface over said rear edge at said portion thereof having a concave contour.

10           30.    The method of claim 29 further comprising providing a trough disposed along said rear edge, and disposing said utility line passing over said rear edge in said trough.

15           31.    A table comprising:  
              a support leg;  
              a worksurface supported by said support leg, wherein said worksurface comprises an upper surface and a rear edge, wherein at least a portion of said rear edge has a concave contour; and  
              a trough disposed along said rear edge below said upper surface of said worksurface.

              32.    The table of claim 31 wherein said trough is attached to said worksurface.

20           33.    A system of tables comprising:  
              a first table comprising a support leg and a worksurface supported by said support leg, wherein said worksurface comprises an upper surface and a rear edge, wherein at least a portion of said rear edge has a concave contour; and  
25               a second table comprising a support leg and a worksurface supported by said support leg, wherein said worksurface comprises an upper surface and a rear edge, wherein at least a portion of said rear edge has a concave contour, wherein said second table is positioned adjacent said first

table with said rear edges thereof substantially abutting, wherein said portions of said rear edges having said concave contours form an opening between said first and second table.

- 5           34.     The system of claim 33 wherein each of said first and second tables comprise a trough disposed along said rear edge of each of said tables below said upper surface of said worksurface of each of said tables.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995